


TWIN-CAT-3

The TWIN-CAT-3 provides an excellent solution for wind-in, wind-out, label reversing and inspection applications. You can also use the TWIN-CAT-3 to count labels, as well as remove waste-matrix when used in conjunction with a CAT-3 Rewinder.

Purchase the base Drive Unit, and then add the Core Holders and other options that you would like.



TWIN-CAT-3

(w/ C76-170, INSP-6, & PCT-1)

Technical Specifications	TWIN-CAT-3	CORE HOLDERS	OPTIONS
Max Roll Diameter (in)	8.6 (218-mm)	6" Width Media (170mm)	<ul style="list-style-type: none"> • PCT-1 (Digital Preset Counter)
Core Diameter (in)¹	Varies	<ul style="list-style-type: none"> • TC-C1.5-170 (1.5" Core. 38mm. Flanges: 1) • TC-C40-170 (1.57" Core. 40mm. Flanges: 1) 	<ul style="list-style-type: none"> • PCT-2 (Digital Preset Scaling Counter)
Max Media Width (in)¹	6 - 10 (152 - 254-mm)	<ul style="list-style-type: none"> • TC-C76-170 (3" Core. 76mm. Flanges: 2) 	<ul style="list-style-type: none"> • INSP-6 (Inspection Fixture, 6". 170mm)
Max Roll Weight (lbs)	15 (6.8-kg)	<ul style="list-style-type: none"> • TC-C100-170 (4" Core. 76mm. Flanges: 1) 	<ul style="list-style-type: none"> • INSP-8 (Inspection Fixture, 8". 220mm)
Dimensions-HWD (in)	19x9x15 (482 x 228 x 381-mm)	<ul style="list-style-type: none"> • ACH-TC3⁴ (1" - 4" Adj. Core. 25-101mm) 	<ul style="list-style-type: none"> • INSP-10 (Inspection Fixture, 10". 270mm)
Weight (lbs)²	40 - 50 (18 - 22.7-kg)	<ul style="list-style-type: none"> • SHAFT, TC-CL (Coreless. Flanges: 2) • SHAFT, TC-1" (1" Core. 25-mm. Flanges: 2) 	<ul style="list-style-type: none"> • FOOTSWITCH (Optional Foot Pedal)
Max Speed (ips)	218 (5537-mm)	<ul style="list-style-type: none"> • SHAFT, TC-W6 (3" Core. 76-mm. Flanges: 2) 	<ul style="list-style-type: none"> • LTO-TC3 (Low Torque Option)
Min Speed (ips)	0.5 (13-mm)	8" Width Media (220mm)	<ul style="list-style-type: none"> • FSPC-TC3 (Permits simultaneous use of the FOOTSWITCH and the automatic stop feature of the Counter.)
Max Torque (in-oz)³	228	<ul style="list-style-type: none"> • TC-C76-220 (3" Core. 76-mm. Flanges: 2) 	
Max RPM³	485	10" Width Media (270mm)	
Number of Flanges¹	Varies	<ul style="list-style-type: none"> • TC-C1.5-270 (1.5" Core. 38mm. Flanges: 1) • TC-C76-270 (3" Core. 76mm. Flanges: 2) 	
Power Specifications	120 - 220VAC in, 19VDC 80W Out	<ul style="list-style-type: none"> • SHAFT, TC-W10 (3" Core. 76mm. Flanges: 2) 	
Warranty	5 year limited warranty on Rewinder - 1 year limited warranty on Power Adaptor and Options		

1. Depends on the Core Holders selected.

2. Depends on the Core Holders and Options selected.

3. **LTO-TC3** decreases Torque Range to 172 - 35 in-oz, and Max RPM to 339.

4. **ACH-TC3** Does not include any Flanges, and cannot be mixed with any other Core Holders.