

1117 MULTI-ISO HF RFID READER FOR MOTOROLA MC55/65/67 SNAP-ON HF RFID READER



High Frequency upgrade

This snap-on accessory provides the Motorola™ MC55/65/67 terminal with High Frequency (HF) RFID functionality. The reader attaches as a snap-on to the Motorola terminal and houses both the RFID reader and the antenna. Power for the reader is obtained from the host terminal.

The HF RFID reader provides the ability to read and write to a wide variety of transponders at 13.56 MHz including ISO 15693, ICODE (I & II) and the complete Mifare family of ISO14443 (A&B). Flash upgradeability of the RFID reader firmware provides future proofing of the reader. The data output from the RFID reader may be simply incorporated into a Pocket PC application using the Software Development Kit (SDK).

Tough enough

Applications include: e-Payment, e-Toll Road Pricing, Authentication, e-Ticketing for Events & Public Transport, Logistics & Supply Chain Management.

The Reader is available individually or as an Explorer kit containing the reader, sample RFID tags and a Software Development Kit (which includes a demonstration application, the source code for that application and full reader documentation)

Features:

Multi ISO RFID reading & writing

Reads and writes to High frequency industry standard ISO 15693 smart labels including Texas Instruments Tag-it™ and Philips ICODE™ II ISO15693 at 13.56 MHz

SDK

Software development kit (SDK) available for development of custom applications.

Compatibility

The reader remains compatible with existing MC55/65/67 accessories such as the single slot cradle and car charger.

Connectivity

USB and MC55/65/67 charge connections are brought through to the base of the HF RFID reader to allow charging and ActiveSync over USB with the Reader attached.

Easy attachment

Customer installable assembly - easily removed from handheld.

SPECIFICATIONS

Physical and Environmental Characteristics

Dimensions:	85×100×30mm (3.35"×3.93"×1.18")
Weight:	100g (3.35 oz)
Enclosure material:	Polycarbonate
Colour:	Black
Material finish:	Sparkled surface
Mechanical attachment:	Snap-on action
Docking:	Attachment maintains dockability with Motorola docking cradle for charging and ActiveSync

HF RFID Reader

Frequency:	13.56MHz																														
Supported RFID Standards:	ISO14443A, ISO14443B, ISO 15693, ISO 18000-3, ICODE																														
Supported Tag-ICs :	<table border="0"> <tr> <td>Tag-it HF-I</td> <td>SRIX4K</td> </tr> <tr> <td>Tag-it HF-I Light S</td> <td>LRI 12</td> </tr> <tr> <td>Philips ICODE SL2</td> <td>LRI 64</td> </tr> <tr> <td>Infineon ISO15693</td> <td>LRI 512</td> </tr> <tr> <td>MIFARE® Standard</td> <td>EM4135</td> </tr> <tr> <td>MIFARE® 4k</td> <td>KSW Temp Sense</td> </tr> <tr> <td>MIFARE® Pro</td> <td>Sharp S</td> </tr> <tr> <td>MIFARE® Ultralight</td> <td>ASK GTML</td> </tr> <tr> <td>MIFARE® DESFIRE</td> <td>ASK GTML2ISO</td> </tr> <tr> <td>MIFARE® SmartMX</td> <td>TOSMART P064</td> </tr> <tr> <td>SLE 55Rxx</td> <td>Jewel Tag</td> </tr> <tr> <td>SRF55VxxP +S</td> <td>(IRT0302B11 KSW)</td> </tr> <tr> <td>SLE 66CL160S</td> <td>ISO14443A Tags</td> </tr> <tr> <td>SLE 66CLX320P</td> <td>ISO14443B Tags</td> </tr> <tr> <td>SR176</td> <td>ISO15693 Tags</td> </tr> </table>	Tag-it HF-I	SRIX4K	Tag-it HF-I Light S	LRI 12	Philips ICODE SL2	LRI 64	Infineon ISO15693	LRI 512	MIFARE® Standard	EM4135	MIFARE® 4k	KSW Temp Sense	MIFARE® Pro	Sharp S	MIFARE® Ultralight	ASK GTML	MIFARE® DESFIRE	ASK GTML2ISO	MIFARE® SmartMX	TOSMART P064	SLE 55Rxx	Jewel Tag	SRF55VxxP +S	(IRT0302B11 KSW)	SLE 66CL160S	ISO14443A Tags	SLE 66CLX320P	ISO14443B Tags	SR176	ISO15693 Tags
Tag-it HF-I	SRIX4K																														
Tag-it HF-I Light S	LRI 12																														
Philips ICODE SL2	LRI 64																														
Infineon ISO15693	LRI 512																														
MIFARE® Standard	EM4135																														
MIFARE® 4k	KSW Temp Sense																														
MIFARE® Pro	Sharp S																														
MIFARE® Ultralight	ASK GTML																														
MIFARE® DESFIRE	ASK GTML2ISO																														
MIFARE® SmartMX	TOSMART P064																														
SLE 55Rxx	Jewel Tag																														
SRF55VxxP +S	(IRT0302B11 KSW)																														
SLE 66CL160S	ISO14443A Tags																														
SLE 66CLX320P	ISO14443B Tags																														
SR176	ISO15693 Tags																														
RF Transmission Speed:	Up to 848 kBit/s																														
Read Distance:	Up to 8cm (3") using ISO7810 size credit card format transponders.																														

SAM support

SAM clock:	3.39MHz
SAM VCC:	5V
SAM type:	Form factor compatible with GSM SIM footprint

Current consumption

Current Consumption:	<p>< 130 mA during RFID read</p> <p>< 65mA in idle mode</p> <p>< 35mA in standby mode</p>
----------------------	--

User indication

Red, Green LEDs:	Flash indicating activity (function may also be customised)
------------------	---

Connection Interfaces

Physical interface:	USB and power in to charge MC55/65/67
Reader power supply:	Powered from host terminal
ActiveSync:	via USB

Environmental

Operating Temp.:	-10°C to +50°C (14°F to 122°F)
Storage Temp.:	-40°C to +70°C (-40°F to 158°F)
Tumble:	250 0.5m tumbles (500 drops)
Drop Spec:	1.2m (4ft) to concrete
Sealing:	IP54
Electrostatic Discharge (ESD):	+/-15kV air discharge, +/-8kV direct discharge
Construction:	RoHS compliant

Supported Operating Systems

Terminal	Supported OEM OS
MC5590	Windows Mobile 6.1, OS 3.38.0004 or higher Windows Mobile 6.5, OS 3.38.0004 or higher
MC55A0	Windows Mobile 6.5, OS 1.34.0005 or higher
MC55N0	Windows Mobile 6.5, OS 1.36.0017 or higher
MC659B	Windows Mobile 6.5, OS 2.31.0002 or higher
MC67*	Windows Mobile 6.5, OS 1.27.36 or higher

*MC67 is supported by TSL 1117 Readers with serial number 1117-002000 or higher

Regulatory

Electrical Safety:	Europe - EN60950-1 with CB Scheme Group and National Differences USA - UL60950-1
EMI/RFI:	EN 302 291-2, EN 301 489-3 USA/Canada - FCC Part 15(c) 15.225 / RSS-210

PART NUMBERS

1117-01-SO-MC65-RFID

1117 Multi-ISO HF RFID Reader for
Motorola MC55/65/67

WARRANTY

Warranty

The TSL 1117 reader is warranted against defects in workmanship and materials for a period of one year (12 months) from date of shipment, provided the product remains unmodified and is operated under normal and proper conditions.

ABOUT TSL

TSL designs and manufactures both standard and custom embedded, snap on and standalone peripherals for handheld computer terminals. Embedded technologies include:

- RFID - Low Frequency, High Frequency & UHF
- *Bluetooth*[®] wireless technology
- Contact Smartcard
- Fingerprint Biometrics
- 1D and 2D Barcode Scanning
- Magnetic Card Readers
- OCR-B and ePassport

Utilizing class leading Industrial design, TSL develops products from concept through to high volume manufacture for Blue Chip companies around the world. Using the above technologies TSL develops innovative products in a timely and cost effective manner for a broad range of handheld devices.

CONTACT

Address:

Technology Solutions (UK) Limited, Suite A,
Loughborough Technology Centre, Epinal Way,
Loughborough, Leicestershire, LE11 3GE,
United Kingdom.

Telephone:

+44 1509 238248

Fax:

+44 1509 214144

Email:

enquiries@tsl.uk.com

Website:

www.tsl.uk.com



ISO 9001: 2008

© Technology Solutions (UK) Ltd 2015. All rights reserved. Technology Solutions (UK) Limited reserves the right to change its products, specifications and services at any time without notice.