

Standard Wax

Efficient Wax Thermal Transfer Ribbon



Food/Beverage



Health/Beauty



Logistics



Retail

Benefits

- Handles general purpose applications with ease
- Highly compatible - no printer adjustments
- Remarkable blackness in print quality
- Good stock latitude from rough to smooth coated papers
- Excellent print quality on food coated labels
- Specially formulated backcoat protects the printhead

Recommended Stocks

Paper

- Vellum
- Matte Coated
- Semi-Gloss
- Gloss
- Floodcoats

Applications

- Compliance labeling
- Component identification
- Hang tags
- Ingredient lists
- Prepared foods
- Prime label
- Product identification
- Shipping
- Warehousing
- Work in Process (WIP)

Technical Specifications

| | |
|------------------------------|--------------------|
| Film Thickness | 4.5 Microns |
| Total Ribbon Thickness | 8.1 Microns |
| Transmission Density | >4.0 MacBeth Scale |
| Ink Melting Point | 67°C / 152°F |

Imaging Characteristics

| | |
|-----------------------|-----------------------|
| Printer | Flathead |
| Max Print Speed | 10 IPS (254 mm/s) |
| Image Darkness | 1.9 RD (densitometer) |

Compliance

- REACH / SVHC 1907/2006/EC
- EU Food Contact 1935/2004/EC
- US Food Contact FDA
- RoHS / Heavy Metals 2011/65/EU
- California Proposition 65
- Halogens IEC 61249-2-21:2003

Storage Conditions

12 months recommended
20-85% Relative Humidity Rate, 23-104°F (-5-40°C)

Performance Ratings

