



Ribbon designed for all paper substrates

Key benefits

- Crisp, dark imaging
- Prints well on smooth and rough papers
- Excellent print quality on flood coated labels

Applications

- Rack identification labels
- Pallet identification labels
- Shipping labels
- Tote and crate labels
- Clothing tags
- And many more...



Recommended substrates

Rough papers	● ● ● ● ●
Coated papers/tags	● ● ● ● ●
Synthetics	● ● ● ○ ○

Print quality

0° barcode	● ● ● ● ●
90° barcode	● ● ○ ○ ○
Small characters	● ● ● ○ ○

Print resistance

Abrasion	● ● ○ ○ ○
Solvent	○ ○ ○ ○ ○
Heat	60°C 140°F

Printer parameters

Maximum speed: 10 ips (250 mm/s)

Heat settings:



Technical specifications

Film thickness: 4,5µm
Total ribbon thickness: <9µm
Ink melting point: 67°C | 153°F
Coefficient of friction: Kd < 0,2
Ink blackness: 1,9 ODR
Antistatic designed

Approvals

REACH / SVHC 1907/2006/EC
EU Food Contact 1935/2004/EC
US Food Contact FDA
RoHS / Heavy Metals 2011/65/EU
California Proposition 65
Halogens IEC 61249-2-21:2003

Storage conditions

- 12 months recommended
- 20-80% Relative Humidity
- 5-35°C (40-95°F) temperature